

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 208 862 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
29.05.2002 Bulletin 2002/22

(51) Int Cl.7: **A61M 5/50**, **A61M 5/32**,
A61B 5/15

(21) Application number: **02003520.0**

(22) Date of filing: **05.06.1997**

(84) Designated Contracting States:
DE ES FR GB IT
Designated Extension States:
AL LT LV MK RO SI

• **DiCesare, Paul**
Norwalk, Connecticut 06851 (US)

(30) Priority: **21.06.1996 US 667681**

(74) Representative: **Selting, Günther, Dipl.-Ing. et al**
Patentanwälte
von Kreisler, Selting, Werner
Postfach 10 22 41
50462 Köln (DE)

(62) Document number(s) of the earlier application(s) in
accordance with Art. 76 EPC:
97109076.6 / 0 813 882

(71) Applicant: **Becton, Dickinson and Company**
Franklin Lakes, New Jersey 07417-1880 (US)

Remarks:

This application was filed on 15 - 02 - 2002 as a
divisional application to the application mentioned
under INID code 62.

(72) Inventors:


• **Mewby, Mark**
Tuxedo, New York 10987 (US)

(54) Needle safety device

(57) A needle assembly having a telescoping shield (3) that extends over the distal end (6) of the needle (2) when released by an actuator (4) that is triggered during a standard sequence of operation of a medical procedure. For example, the telescoping shield (3) extends by means of a compression spring (19) from a starting retracted position to a venipuncture partially extended

position during the standard sequence of operation of drawing a blood sample with an evacuated blood collection tube (50) and needle holder (20). After the procedure is complete and the needle is removed from the patient the shield (3) continues to extend to a fully extended and locked position over the distal end (6) of the needle (2) rendering the needle safe and preventing needle stick injuries.

FIG-4



EP 1 208 862 A1

BEST AVAILABLE COPY

Printed by Jouve, 75001 PARIS (FR)

Description

1. Field of the Invention

[0001] The present invention relates to a safety needle with a telescoping shield that is triggered during a standard sequence of operation of a medical procedure and, more particularly, relates to a needle and hub assembly having a telescoping shield that is triggered when an evacuated tube is mounted in the evacuated tube needle holder.

[0002] An evacuated collection tube, needle and needle holder are commonly used by a doctor, phlebotomist or nurse to draw a sample of body fluid from a patient in a hospital or doctor's office for diagnostic testing. During the use of such a needle holder, the distal end of the needle in the needle holder is inserted in a vein of the patient. The evacuated collection tube is then inserted into the proximal end of the needle holder until a needle within the holder pierces a closure on the end of the tube. The vacuum in the tube then draws a body fluid sample from the patient through the needle and into the tube. After the collection process is complete the needle is removed from the vein and disposed of.

[0003] Because of the great concern that users of such needles may be contaminated with the blood of a patient by accidental sticks from the contaminated needle, it is preferable to cover the contaminated needle as soon as it is removed from the vein. For this reason, many developments have been made to provide means for covering the contaminated needle, once it is removed from the patient. These devices usually involve some sort of shield arrangement that moves in place over the contaminated needle once it has been removed from the patient. However, these shield arrangements have required the use of one or two hands to perform the operation of moving the shield over the contaminated needle, which is a hindrance to the user.

[0004] Alternatively, needles with internal or external blunting cannulas have been used that extend from the needle to blunt the distal end. However, these devices require an additional manual operation to drive the blunting cannula over or out of the needle upon completion of blood drawing to protect the user from the sharp end of the needle and also allow the user to draw blood without triggering the safety device. Such devices also require the internal diameter of the needle to be decreased which may affect blood flow or require the external diameter of the needle to be enlarged which may cause unnecessary discomfort to the patient.

[0005] Other needles have shields that are activated during the venipuncture operation when the shield comes in contact with the skin. Using the skin to activate the device is not desirable since the device may not activate if the needles does not penetrate sufficiently or may cause the shield to inadvertently lock when probing for the vein. Such devices may also require excessive penetration into some patients to cause the triggering

means to activate the device which will cause a phlebotomist to unnecessarily have to change their standard method or procedure.

[0006] EP 0 680 767 A1 discloses a needle assembly having the features of the precharacterizing part of claim 1. The needle assembly comprises a needle hub fixed to a syringe, and a telescoping shield slidably mounted on the syringe. The syringe is biased by a compression spring so that by releasing the spring the needle is withdrawn into the shield. The torsion spring is held in its biased state by elastic tongues supporting the syringe. Said tongues are pushed radially outward when a piston is moved forward within the syringe. Thus, during use of the syringe, the needle shield is released and is locked in the distal position where it covers the needle tip.

[0007] It is an object of the present invention to provide a needle shield that is automatically activated with the normal procedure used during blood collection.

[0008] The needle assembly of the present invention is defined by claim 1.

[0009] For example, the safety needle incorporates a telescoping shield that extends by means of a compression spring from a starting retracted position to a venipuncture partially extended position during the standard sequence of operation of drawing a blood sample with an evacuated blood collection tube and needle holder. In particular, when the closure or stopper on the collection tube compresses a rubber multiple sample sleeve on the proximal end of the needle, an actuator is triggered by the closure and/or sleeve to cause the telescoping shield to extend. Then, when the needle is removed from the patient the shield continues to extend to a fully extended and locked position over the distal end of the needle rendering the needle safe and preventing needle stick injuries.

[0010] The needle assembly of a preferred embodiment of the present invention consists of a double ended needle, cannula having a distal end for venipuncture and a proximal end for puncture of the closure on the evacuated blood collection tube. The needle is retained within a needle hub that attaches to the needle holder and includes the compression spring, an actuator and a telescoping shield. The elastomeric or rubber multiple sample sleeve encompasses the proximal end of the needle cannula. Upon insertion of the evacuated blood collection tube into the needle holder the closure and/or sleeve drives the actuator linearly in the distal direction through a slot in the needle hub. An arm on the distal end of the actuator includes a cam face that engages with a mating surface on a lug at the proximal end of the telescoping shield. The surfaces interact to rotate the shield out of the starting retracted position into a channel whereby the shield is pushed by the compression spring down the length of the cannula to a venipuncture partially extended position. The rotation also loads a torsion spring on the shield to maintain the shield in a loaded/torqued position when at the venipuncture partially ex-

tended position. When venipuncture is complete and the needle is withdrawn from the patient, the shield is further extended by the compression spring to the fully extended position. In that position the shield rotates due to the torsion spring to move the lug on the shield from the channel over a ramp and into a distal locking pocket on the needle hub. When the lug is in the locking pocket the shield sufficiently covers the distal end of the needle cannula and renders the needle assembly safe.

[0011] Of course, the present invention is not limited to activation by a blood collection tube since it would be equally functional on a syringe with activation by syringe plunger or on a catheter with activation when the introducer needle is retracted and removed from the catheter device.

[0012] These and other aspects, features and advantages of the present invention will become apparent from the following detailed description taken in conjunction with the accompanying drawings.

DESCRIPTION OF THE DRAWINGS

[0013]

Fig. 1 is a perspective view of a needle assembly according to the present invention in a starting retracted position;

Fig. 2 is a perspective view of the needle assembly shown in Fig. 1 mounted on a needle holder;

Fig. 3 is a partial cross-sectional view of the needle and holder assembly shown in Fig. 2 in the starting retracted position;

Fig. 4 is a partial cross-sectional view of the needle and holder assembly shown in Fig. 2 in a venipuncture partially extended position;

Fig. 5 is a partial cross-sectional view of the needle and holder assembly shown in Fig. 2 in a fully extended and locked position;

Fig. 6 is a partial perspective view of the needle hub;

Fig. 7 is a cross-sectional view of the needle assembly shown in Fig. 3 along lines 7-7;

Fig. 8 is a cross-sectional view of the needle assembly shown in Fig. 4 along lines 8-8; and

Fig. 9 is a cross-sectional view of the needle assembly shown in Fig. 5 along lines 9-9.

DETAILED DESCRIPTION

[0014] Fig. 1 is a perspective view of a needle assembly 1 according to the present invention in a starting re-

tracted position. Assembly 1 includes a needle cannula 2 mounted in a needle hub 5 having a telescoping shield 3 mounted thereon for movement from a starting retracted position (Figs. 3 and 7) through a venipuncture partially extended position (Figs. 4 and 8) to a fully extended and locked position (Figs. 5 and 9) covering a distal end 6 of needle cannula 2. A proximal end 7 of needle cannula 2 is encompassed by an elastomeric or rubber multiple sample sleeve 8 that is attached to a distal end of needle hub 5 to seal proximal end 7 and prevent fluid from flowing through cannula 2.

[0015] Assembly 1 also includes an actuator 4 having a sleeve 14 and a pair of arms 15 that are used to trigger telescoping shield 3 for transport from its starting retracted position to its final fully extended and locked position. As shown in Fig. 1 and described further below, telescoping shield 3 includes a torsion spring 13 having a tab 12 that travels in a longitudinal track 53 on needle hub 5. Shield 3 also includes a pair of lugs 11 that travel in longitudinal channels 54 on needle hub 5 and interact with arms 15 on actuator 4 to trigger movement of telescoping shield 3, when actuator 4 is pushed in the distal direction.

[0016] Fig. 2 is a perspective view of needle assembly 1 mounted in needle holder 20. Needle holder 20 includes a proximal end 21 and a distal end 23 wherein proximal end 21 includes an opening 22 for receiving an evacuated blood collection tube 50 (Fig. 4) having a closure 51. As more clearly shown in Fig. 3, needle hub 5 on needle assembly 1 includes a flange 9 and a plurality of threads 17 that mate with a plurality of threads 18 in distal end 23 of needle holder 20 to fasten or otherwise attach needle assembly 1 to needle holder 20.

[0017] Fig. 3 is a partial cross-sectional view of needle assembly 1 and needle holder 20 with needle assembly 1 in the starting retracted position. In the starting retracted position, cannula 2 extends from a distal end 35 of needle shield 3 so that distal end 6 of cannula 2 is ready for insertion through a patient's skin and into a vein. In the starting retracted position, since no blood collection tube 50 and closure 51 have been inserted into needle holder 20, actuator 4 has not been pushed or moved in the distal direction and shield 3 has not been triggered or activated.

[0018] As more clearly shown in Fig. 3, each of arms 15 extending in the distal direction from sleeve 14 on actuator 4 include cam faces 10 that are aligned with and/or adjacent to corresponding mating surfaces 16 on the proximal ends of lugs 11 on shield 3. Cam face 10 and mating surface 16 are arranged to interact with each other to trigger movement of telescoping shield 3 out of the starting retracted position when actuator 4 is pushed in the distal direction. In particular, as actuator 4 is pushed in the distal direction, cam face 10 mates with mating surface 16 to cause lug 11 and shield 3 to rotate in the direction of arrow A in Fig. 7, which allows shield 3 to begin movement down needle hub 5 in the distal direction. The force needed to move or transport shield

3 down needle hub 5 in the distal direction to the venipuncture partially extended position shown in Fig. 4, described below, is provided by a compression spring 19 mounted within needle hub 5.

[0019] Fig. 4 shows needle assembly 1 in the venipuncture partially extended position where distal end 6 of needle cannula 2 has punctured a patient's skin 30 and needle assembly 1 has been triggered by movement of actuator 4 in the distal direction. Needle assembly 1 is triggered by the insertion of an evacuated blood collection tube 50 having a closure 51 into needle holder 20, when a top surface 52 of closure 51 compresses multiple sample sleeve 8 after it has been penetrated by proximal end 7 of needle cannula 2. When multiple sample sleeve 8 is compressed by closure 51, sleeve 8 and/or closure 51 interact with and push sleeve 14 of actuator 4 in the distal direction to cause cam surface 10 on arm 15 to mate with mating surface 16 on lug 11 of shield 3. When these surfaces interact, shield 3 is rotated in the direction of arrow A (Fig. 7) and lug 11 is pushed out of a proximal pocket 56 (Fig. 6) in needle hub 5 and into a channel 54 (Fig. 6) in needle hub 5.

[0020] After lug 11 has moved into channel 54 compression spring 19 (Fig. 5) transports shield 3 in the distal direction until distal end 35 of shield 3 makes contact with the patient's skin surface 30, as shown in Fig. 4. The phlebotomist can then continue to draw body fluid samples into one or more evacuated collection tubes 50 by easily removing and replacing evacuated tubes 50 until sufficient body fluid has been drawn. The present invention, therefore, permits the user to perform the medical procedure without changing their normal sequence of operation, since no conscious action is needed to activate or otherwise control telescoping shield 3. It should be understood that telescoping shield 3 is triggered and transported to the partially extended position merely by pushing closure 51 onto distal end 7 of cannula 2 and/or compressing multiple needle sleeve 8. After actuator 4 has triggered and transported telescoping shield 3 from the retracted position shown in Fig. 3 to the partially extended position shown in Fig. 4, needle assembly 1 is ready to transport telescoping shield to the fully extended position shown in Fig. 5 when cannula 2 is removed from the patient's skin 30.

[0021] Fig. 5 is a partial cross-sectional view of needle assembly 1 and needle holder 20 showing needle assembly 1 in the fully extended and locked position. In this position shield 3 is fully extended such that distal end 35 of shield 3 extends beyond distal tip 6 of cannula 2. Fig. 5 also shows a proximal seat 33 in needle hub 5 and a distal seat 34 in shield 3 for each respective end of compression spring 19 in its fully extended state where it has fully transported shield 3 from the starting retracted position (Fig. 3) through the venipuncture partially extended position (Fig. 4) and finally to the fully extended and locked position (Fig. 5). Fig. 5 also shows lug 11 located in distal pocket 55 (Figs. 6 and 9) which together provide means

for locking shield 3 in the fully extended position.

[0022] Fig. 6 is a partial perspective view of needle hub 5 having a distal end 61 and a proximal end 62. Fig. 6 provides a better view of longitudinal channel 54 and proximal pocket 56 at proximal end 62 and distal pocket 55 at distal end 61. In addition, Fig. 6 shows longitudinal track 53 which is arranged to receive and guide tab 12 on torsion spring 13 as shield 3 moves from the starting retracted position (Fig. 3) through the venipuncture partially extended position (Fig. 4) and finally to the fully extended and locked position (Fig. 5), where torsion spring 13 causes shield 3 to rotate in the direction of arrow B (Fig. 9) and move lugs 11 into their respective distal pockets 55 on needle hub 5.

[0023] Fig. 7 is a cross-sectional view of needle assembly 1 shown in Fig. 3 at its starting retracted position along lines 7-7. As shown in Fig. 7, tab 12 of torsion spring 13 is located in torsion spring track 53 in needle hub 5 and each shield lug 11 is located in a respective proximal pocket 56. Each of these lugs 11 are held in each pocket 56 by a respective retention rib 57. When closure 51 is penetrated by distal end 7 of cannula 2 and sleeve 14 on actuator 4 causes distal lateral movement of actuator 4 and mating of surfaces 10 and 16, shield 3 is rotated in the direction of arrow A and lugs 11 move over retention ribs 57 into their respective channels 54. Once lugs 11 are in their respective channel 54, compression spring 19 causes distal movement of shield 3 until it reaches the partially extended position shown in Fig. 4. Fig. 8 is a cross-sectional view of needle assembly 1 shown in Fig. 4 along lines 8-8, that more clearly shows lugs 11 in channels 54 and tab 12 of torsion spring 13 in track 53. Fig. 8 also more clearly shows torsion spring 13 under torque due to the rotation of shield 3 in the direction of arrow A.

[0024] After venipuncture and withdrawal of cannula 2 from the patient's skin 30, shield 3 moves to its fully extended and locked position shown in Fig. 5. As more clearly shown in Fig. 8, a cross-sectional view of needle assembly 1 shown in Fig. 5 along lines 8-8, each lug 11 is located and locked in a respective distal pocket 55 by a locking ramp 58. In particular, lugs 11 have moved from channels 54 over locking ramps 58 and into distal pockets 55 by rotation of shield 3 in the direction of Arrow B because of the torque on torsion spring 13. Fig. 8 also shows tab 12 on torsion spring 13 located in track 53, but no longer under torque.

[0025] Alternatively, rotation of shield 3 would not be needed when distal pocket 55 and proximal pocket 56 are axial with longitudinal channels 54. In such a structure arm 15 on actuator 4 would lift lug 11 out of proximal pocket 56 to trigger movement of shield 3 out of the retracted position. After venipuncture lug 11 would move axially down channel 54 and into distal locking pocket 55 to lock shield 3 in the fully extended position. Torsion spring 13 would not be needed since no rotation is necessary. Of course, other variations could be used and still fall within the scope of the present invention, such

as, combining an axial pocket with a pocket requiring rotation.

[0026] The above described needle assembly 1 with its telescoping shield 3 is used by a phlebotomist in the following manner and method. After a user has removed needle assembly 1 from its sterile package, it is snap mounted or screw mounted onto distal end 23 of needle holder 20 using threads 17 and 18 until flange 9 comes into contact with distal end 23 of needle holder 20. The user then prepares a venipuncture site on the patient's skin 30 and applies a tourniquet prior to venipuncture.

[0027] Venipuncture is then performed by inserting distal end 6 of needle cannula 2 into patient's skin 30 and into a vein. When distal end 6 has been properly inserted and evacuated blood collection tube 50 with its closure 51 is inserted into open end 22 of needle holder 20, closure 51 is then punctured by proximal end 7 of needle cannula 2. When puncture of closure 51 has occurred sufficiently to contact and move actuator 4 in a distal direction, cam face 10 on arm 15 of actuator 4 meets with mating surface 16 on lug 11 of shield 3 to cause shield 3 to rotate in direction A and activate transportation of shield 3 in the distal direction toward the venipuncture site and into the partially extended position.

[0028] In addition to activating telescoping shield 3, when proximal end 7 enters into evacuated tube 50 body fluid flows through cannula 2 into evacuated tube 50 and when sufficient body fluid has been received the user can remove evacuated tube 50 from tube holder 20 and continue drawing body fluid with additional evacuated blood collection tubes 50. When evacuated blood collection tube 50 is removed from needle holder 20 multiple sample sleeve 8 returns to its original position to close and seal distal end 7 of cannula 2 and stop the flow of body fluid through cannula 2. When no more body fluid is desired to be collected, needle cannula 2 is withdrawn from the patient's vein and skin 30 permitting shield 3 to further extend to the fully extended and locked position shown in Fig. 5, where distal end 35 of shield 3 extends beyond and sufficiently shields distal end 6 of needle cannula 2.

[0029] In the foregoing discussion, it is to be understood that the above-described embodiments of the present invention are merely exemplary. For example, the distal locking pocket can alternatively be located linearly in the channel at the distal end of the needle hub to alleviate the need for rotation by the torsion spring. In addition, of course, the present invention is not limited to activation by a blood collection tube since it would be equally functional on a syringe with activation by syringe plunger rod or on a catheter with activation when the introducer needle is retracted and removed from the catheter device. Other suitable variations, modifications and combinations of the above described features could be made to or used in these embodiments and still remain within the scope of the present invention.

Claims

1. A needle assembly comprising:

- 5 a needle cannula (2) having a distal end (6) and a proximal end (7);
- a needle hub (5) in which said needle cannula (2) is mounted;
- 10 a telescoping shield (3) slidably mounted on said needle hub (5) and comprising a lug (11) having a lug surface (16);
- 15 means (19) for transporting said telescoping shield (3) from a retracted position to a partially extended position and finally to the fully extended and locked position;
- 20 means (11,55) for locking said telescoping shield (3) in the fully extended position; and
- 25 an actuator (4) slidably mounted relative to said needle hub (5) and comprising a cam surface (10) for engaging with said lug surface (16) of said telescoping shield (3), whereby said telescoping shield is moved out of the retracted position when said proximal end of said actuator (4) is activated by pressure applied during a standard sequence of operation of a medical procedure,
- 30

characterized in that

said cannula is a double ended needle for mounting in a needle holder (20), with a distal end (6) for performing venipuncture and a proximal end (7) for puncturing the closure (51) of an evacuated blood collection tube (50); and
said needle assembly further comprising a multiple sample sleeve (8) mounted on said proximal end (7) of said cannula (2) to seal said proximal end and activate said actuator (4) when the closure (51) is punctured by said proximal end of said cannula.

2. The needle assembly of claim 1 characterized in that

the needle hub (5) comprises a longitudinal channel (54) comprising a proximal pocket (56) for receiving said lug (11) when said telescoping shield (3) is in the retracted position, and a distal locking pocket (55) for receiving said lug (11) when said telescoping shield (3) is in the fully extended position, said locking means (11,55) includes said distal locking pocket (55) on said needle hub (5) which prevents said telescoping shield (3) from leaving the fully extended and locked position, and
said needle hub (5) comprises means (13) for rotating said telescoping shield (3) to cause said lug (11)

on said telescoping shield (3) to rotate from said channel (54) into said distal locking pocket (55).

3. A needle assembly according to claim 2, wherein said rotating means comprises a torsion spring (13) including a tab (12) extending towards said needle hub (5). 5
4. A needle assembly according to claim 3, wherein said needle hub (5) includes a track (53) for receiving the tab (12) of the torsion spring (13) whereby, when a rotational force is applied to said telescoping shield (3) by said torsion spring, said lug (11) on said telescoping shield rotates from said channel (54) on said needle hub (5) into said distal locking pocket (55) on said needle hub. 10 15
5. A needle assembly according to one of claims 1-4, wherein said transporting means includes a spring (19). 20
6. A needle assembly according to claim 5, wherein said spring (19) is a compression spring. 25

25

30


35

40

45

50

55



BEST AVAILABLE COPY






FIG-3




BEST AVAILABLE COPY

FIG-4



BEST AVAILABLE COPY

FIG-5



BEST AVAILABLE COPY




FIG-6

NOT AVAILABLE COPY

8
 1
 6
 7




FIG-7





FIG-9





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 00 3520

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
Y	US 4 887 998 A (MARTIN ET AL.) 19 December 1989 (1989-12-19) * the whole document *	1,5,6	A61M5/50 A61M5/32 A61B5/15
Y	EP 0 286 087 A (ICU MEDICAL, INC.) 12 October 1988 (1988-10-12) * column 6, line 30 - line 36; figure 10 *	1,5,6	
A,D	EP 0 680 767 A (RIGHI ET AL.) 8 November 1995 (1995-11-08) * column 8, line 35 - line 58 * * abstract; figures 1,2,6 *	1,5,6	
A	US 5 176 656 A (BAYLESS) 5 January 1993 (1993-01-05) * column 5, line 13 - line 18; figures 1-3 *	1	
A	EP 0 497 220 A (PETRUSSA) 5 August 1992 (1992-08-05) * column 5, line 33 - line 54; figures 1,2,4 *	1	
A	GB 2 270 471 A (HSIAN-TZUO) 16 March 1994 (1994-03-16) * figures 15-17 *	2	
A	US 4 874 383 A (MCNAUGHTON) 17 October 1989 (1989-10-17) * figures *	2	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 8 April 2002	Examiner Sedy, R
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

EPO FORM 1503 (03.82) (F04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 00 3520

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

08-04-2002

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4887998	A	19-12-1989	NONE	
EP 286087	A	12-10-1988	US 4782841 A	08-11-1988
			CA 1308322 A1	06-10-1992
			EP 0286087 A2	12-10-1988
			JP 63279824 A	16-11-1988
EP 680767	A	08-11-1995	CA 2123278 A1	11-11-1995
			US 5562624 A	08-10-1996
			EP 0680767 A1	08-11-1995
US 5176656	A	05-01-1993	NONE	
EP 497220	A	05-08-1992	IT 1248125 B	05-01-1995
			AT 137122 T	15-05-1996
			DE 69210060 D1	30-05-1996
			DE 69210060 T2	24-10-1996
			EP 0497220 A1	05-08-1992
			US 5376080 A	27-12-1994
GB 2270471	A	16-03-1994	NONE	
US 4874383	A	17-10-1989	CA 1285441 A1	02-07-1991
			AU 620396 B2	20-02-1992
			AU 3380989 A	01-11-1990
			EP 0394537 A1	31-10-1990
			US 5024660 A	18-06-1991

EPO FORM P459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82